



PRODUCT SPECIFICATIONS

TubeTrace[®] Type SP/MP

“HEAVY” STEAM TRACED INSTRUMENT TUBING

APPLICATION

Freeze protection or process temperature maintenance with a tube temperature range: 40°F (5°C) to 400°F (205°C). Designed to provide freeze protection or temperature maintenance for metallic and non-metallic tubing with “heavy” steam trace, TubeTrace Type SP/MP is suitable for use with process analyzers, emissions analyzers, and impulse lines to flow or pressure transmitters where steam or hot liquid is the preferred heating media.

TubeTrace Type SP/MP “heavy” steam trace is a metallic tracer tube that is in direct contact with the process tube(s). The tracer tube and process tube(s) are cabled together thereby mechanically binding the tubes. This ensures consistent heat transfer and performance along the entire length by preventing separation or tube migration within the bundle.

Unlike field fabricated and insulated tubing, TubeTrace engineered pre-insulated tubing provides superior weather proofing and long term reliability.

RATINGS

SP and MP “Heavy” Trace	Ratings
Available Tracer Tube Diameters	1/4”, 3/8” and 1/2”
Available Tracer Tube Materials	Copper and Stainless Steel
Typical Process Tube Temperature	40°F to 250°F (5°C to 205°C)
Maximum Steam Temperature	400°F/235 psig (205°C/1690 kPa)
Typical Temperature Difference Tracer Tube vs. Process Tube	Less Than 25°F (14°C) ⁴



CONSTRUCTION

- 1 Process tube(s)
- 2 Tracer tube
- 3 Heat reflective tape
- 4 Non-hygroscopic glass fiber insulation
- 5 Polymer outer jacket

PRODUCT FEATURES

- Consistent heat transfer and thermal performance
- Superior weather proofing
- Long coils minimize waste

HOW TO SPECIFY

SP - 4F1-3B1 - ATP - 035 / 035

<p>TubeTrace Type</p> <p>SP = Single Tube MP = Multiple Tubes</p>	<p>Process Tube(s) O.D.</p> <p>1 = 1/8" 2 = 1/4" 3 = 3/8" 4 = 1/2" 5 = 5/8" 6 = 3/4"</p>	<p>Process Tube(s) Material</p> <p>A = 316 SS Welded C = PFA Teflon¹ D = Monel² E = Titanium F = 316 SS Seamless G = 304 SS Welded H = 304 SS Seamless J = Alloy C276 K = Alloy 825 L = Alloy 20 M = FEP Teflon T = TFE Teflon X = Special</p>	<p>Number of Process Tube(s)</p> <p>1 2 3</p>	<p>Tracer Tube O.D.</p> <p>2 = 1/4" 3 = 3/8" 4 = 1/2"</p>	<p>Tracer Tube Material</p> <p>A = 316 SS Welded B = 122 Copper F = 316 SS Seamless</p>	<p>Bundle Jacket</p> <p>ATP³ TPU</p>	<p>Number of Tracer Tube(s)</p> <p>1</p>	<p>Process Tube(s) Wall Thickness</p> <p>028 = .028" (SS Only) 035 = .035" 040 = .040" (Plastic Only) 047 = .047" (Plastic Only) 049 = .049" 062 = .062" (Plastic Only) 065 = .065" 083 = .083" (SS Only)</p>	<p>Tracer Tube(s) Wall Thickness</p> <p>032 = .032" 035 = .035" 049 = .049" 065 = .065"</p>
--	---	---	--	--	--	--	---	--	--

Notes . . .

1. Teflon is a trademark of E. I. duPont de Nemours Co., Inc.
2. Monel is a trademark of Inco Alloys International, Inc.
3. Black ATP is standard; other jacket materials are available.
4. Please contact factory for performance data when using for critical temperature applications.

THERMON The Heat Tracing Specialists[®]

ISO 9001 REGISTERED Corporate Headquarters: 100 Thermon Dr • PO Box 609 San Marcos, • TX 78667-0609 • Phone: 512-396-5801 • 1-800-820-4328
For the Thermon office nearest you visit us at . . . www.thermon.com