



PRODUCT SPECIFICATIONS

# Systems Accessories

## THERMON HEAT TRACING CABLES

### TERMINATOR™ NONMETALLIC POWER CONNECTION, SPLICE AND END-OF-CIRCUIT LIGHT KITS

Terminator nonmetallic accessories are approved for ordinary and Division 2 hazardous locations. Terminator ZP, ZS/ZE, ZE-B, and ZL kits certified as Ex e II are also available. The kits have a maximum pipe exposure temperature rating of 482°F (250°C) with a minimum installation temperature of -76°F (-60°C).



**Terminator DP/ZP** is designed to fabricate power connections, in-line/T-splice connections or for making end terminations. Electrical connections are made in terminal blocks utilizing nickel-plated copper terminals to ensure corrosion-free electrical integrity. The up front positioning of the terminal block permits easy access during assembly and for future routine maintenance.

The Terminator DP/ZP kit includes: Type 4X junction box with integral gasket, three-point DIN mount terminal block with nickel-plated copper terminals (600 V, 50 A), pipe-mounted fitting, stainless steel pipe attachment band for piping 10" or less. (PETK/SCTK termination kit required, order separately)

**DP/ZP** .....BSX, RSX, HTSX, VSX, HPT, FP  
**DP-M** .....TEK, HTEK



**Terminator DS/DE and ZS/ZE** are designed to fabricate in-line splices or end terminations.

**Terminator DE-B and ZE-B** are designed to provide visual indication of an energized heating circuit.

Electrical connections are made using wire fasteners. Once the kit is assembled, a tool is required to remove the cover to gain access for maintenance or testing. (For applications requiring terminations to be made with terminal block connections, the Terminator DP or DL kit may be used.)

The Terminator DS/DE, ZS/ZE and DE-B, ZE-B kits include: Type 4X pipe-mounted fitting with locking splice cover, stainless steel pipe attachment band for piping 10" or less. (PETK/SCTK termination kit required, order separately)

**DS/DE, ZS/ZE** .....BSX, RSX, HTSX, VSX, HPT, FP  
**DE-B, ZE-B** .....BSX, RSX, HTSX, VSX, HPT, FP



**Terminator DL and ZL** are designed to provide visual indication of an energized heating circuit. The kit may be utilized as a power connection or an end termination kit. Electrical connections are made in terminal blocks utilizing nickel-plated copper terminals to ensure corrosion-free electrical integrity.

The Terminator DL and ZL kit includes: Type 4X junction box, yellow raised light, diode indicating lamp can be energized with up to 254 Vac without change in luminosity, three-point DIN mount terminal block with nickel-plated copper terminals, pipe-mounted fitting, stainless steel pipe attachment band for piping 10" or less. (PETK termination kit required, order separately)

**DL, ZL** .....BSX, RSX, HTSX, VSX, HPT, FP

### METALLIC POWER CONNECTION, SPLICE AND END-OF-CIRCUIT LIGHT KITS

Thermon metallic accessories utilize aluminum junction boxes and expeditors and are approved for ordinary and Division 2 hazardous locations. The kits have a maximum pipe exposure temperature rating of 500°F (260°C) with a minimum installation temperature of -60°F (-51°C).



**ECA-1** is designed for connecting one or two heating cables to power or for splicing two cables together.

The ECA-1 kit includes: epoxy-coated Type 4X/7 junction box, pipe-mounted expeditor, 2 stainless steel pipe attachment bands for piping 4" or less, heater cable grommet, 2 power connection boots, RTV adhesive, wire fasteners and grounding lug.

**ECA-1-SR** .....BSX, RSX, HTSX, VSX  
**ECA-1-ZN** .....FP, HPT



**ECT-2** is designed for connecting three heating cables to power or for splicing three cables together.

The ECT-2 kit includes: epoxy-coated Type 4X/7 junction box, pipe-mounted expeditor, third cable entry assembly, 2 stainless steel pipe attachment bands for piping 4" or less, heater cable grommets, 3 power connection boots, RTV adhesive, wire fasteners and grounding lug.

**ECT-2-SR** .....BSX, RSX, HTSX, VSX  
**ECT-2-ZN** .....FP, HPT

### TRACEPLUS™ NONMETALLIC KITS

Approved for ordinary and Division 2 hazardous locations.

Max. Exposure Temp. 400°F (204°C)  
 Min. installation Temp. of -20°F (-29°C)



**PCA** is designed to fabricate power connections, in-line/T-splice connections or for making end terminations.

The PCA kit includes: Type 4X junction box, pipe-mounted expeditor, 2 stainless steel pipe attachment bands for piping 10" or less. (PETK/SCTK termination kit required, order separately)

**PCA-H** .....BSX, HTSX, HPT, FP  
**PCA-V** .....RSX, VSX

## THERMON The Heat Tracing Specialists®



Corporate Headquarters: 100 Thermon Dr • PO Box 609 San Marcos, TX 78667-0609 • Phone: 512-396-5801 • 1-800-820-4328  
 For the Thermon office nearest you visit us at . . . [www.thermon.com](http://www.thermon.com)



PRODUCT SPECIFICATIONS

# Systems Accessories

THERMON HEAT TRACING CABLES

## CABLE END TERMINATION KITS, ATTACHMENT TAPES AND MISCELLANEOUS ITEMS



**PETK** circuit fabrication kit includes a power boot, end cap, RTV adhesive.

**SCTK** splice connection/termination kit includes power boots, wirenuts, RTV adhesive.

**PETK-1D / SCTK-1D**.....BSX, RSX, V SX

**PETK-2D / SCTK-2D**.....K SX, HT SX

**PETK-3D / SCTK-3D**.....FP, HPT



**ET-6C, ET-8C** end termination kits are designed to properly terminate the end (away from power) of a heat tracing circuit. Each kit includes a rubber end cap, RTV adhesive and caution label.

**ET-6C** .....BSX, RSX, V SX

**ET-8C** ..... HT SX, K SX, FP & HPT (OJ)



**CL** vinyl-based peel and stick caution labels are intended for direct exposure to industrial environments. Electrically heated pipelines and vessels are to be clearly identified at frequent intervals. Caution labels should be placed at 10'-20' (3-6 m) intervals or as required by code or specification.

**B-4, B-10, B-21** stainless steel attachment bands for securing Thermon connection kits to pipes. Each connection kit includes two bands.

**B-4** for pipes up to 4" (100 mm) diameter

**B-10** for pipes up to 10" (250 mm) diameter

**B-21** for pipes up to 21" (530 mm) diameter



**FT-1L, FT-1H** fixing tapes for attaching heating cable to piping every 12" (30 cm) or as required by code or specification.

**AL-20L, AL-20H, AL-30L, AL-30H** aluminum tape for continuous (longitudinal) covering.

Catalog #	Temp. Max.	Min. Install	Dimensions
FT-1L	200°F	40°F	1/2" x 108'
FT-1H	500°F	-40°F	1/2" x 108'
AL-20L	150°F	40°F	2" x 150'
AL-20H	300°F	20°F	2" x 180'
AL-30L	150°F	40°F	3" x 150'
AL-30H	300°F	20°F	3" x 180'

Note: FT-1H is recommended for use on stainless steel piping and tubing applications.